

Page 1 of 6 POC-9007C

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 1.1 SDS Revision Date: 12/14/2019 1. PRODUCT & COMPANY IDENTIFICATION 11 Product Name PETRA AUTO AIR CONDITIONER EVAPORATOR ODOR ELIMINATOR 1.2 Chemical Name: Aerosol 1.3 Synonyms: 9007C 1.4 Trade Names: Petra Auto Air Conditioner Evaporator Odor Eliminator 1.5 Product Use: Odor Eliminator Distributor's Name: 1.6 Petra Oil NZ 50 Jacobs Lane, Ngaruawahia 3792, New Zealand 1.7 Distributor's Address 1.8 Emergency Phone: NZ NATIONAL POISONS CENTRE (0800) 764 766 Tel: +64 (21) 771 703 1.9 Business Phone / Fax: 2. HAZARDS IDENTIFICATION Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of WHSR and ADG Code (Australia). DANGER! PRESSURIZED CONTAINER: MAY BURST IF HEATED, CAUSES MILD SKIN IRRITATION. CAUSES EYE IRRITATION. Classification: Aerosols 3, Skin Irrit. 3, Eye Irrit. 2B 2.2 Label Elements: Hazard Statements (H): H229 - Pressurized container: may burst if heated. H316 - Causes mild skin irritation. H320 - Causes eye irritation. Precautionary Statements (P): P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 - Pressurized container: Do not pierce or burn, even after use. P264 - Wash affected areas thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P280 - Wear protective gloves/eye protection. P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. Other Warnings: In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. If medical advice is needed, have product container or label at hand. KEEP OUT OF REACH OF CHILDREN. 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-RTECS No. STEL PEL STEL CHEMICAL NAME(S) CAS No. **EINECS No.** TLV **TWA** STEL PEAK **IDLH** OTHER 7732-18-5 ZC0110000 231-791-2 NA NA NF NF NA NA NA WATER 106-97-8 EJ4200000 203-448-7 1-5 1000 900 (800) 1900 NF 800 900 NA BUTANE Press. Gas, Flam. Gas 1; H220; HSNO: HSR000989 111-76-2 KJ8575000 203-905-0 50 75 (20) 96.9 NF 50 75 1-5 700 2-BUTOXYETHANOL Acute Tox. 4 (oral); Acute Tox. 4 (dermal); Acute Tox. 4 (inh); Eye Irrit. 2; Skin Irrit. 2; H332, H312, H302, H319, H315; HSNO HSR001154 151-21-3 WT1050000 205-788-1 1-5 NA NA NF NF NF NA NA SODIUM DODECYL SULPHATE Acute Tox. 4 (oral), Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H302, H315, H318, H412; HSNO: HSR003122 74-98-6 TX2275000 203-448-7 1-5 1000 NA NF NF NF 1000 NA **PROPANE** Press. Gas, Flam. Gas 1; H220; HSNO: HSR001010 4. FIRST AID MEASURES First Aid: Ingestion: Rinse mouth, DO NOT INDUCE VOMITING. Contact Poison Control Center or local emergency telephone number for assistance and instructions. If you feel unwell, seek medical advice (show the label where possible). If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Remove contact lenses, if present and easy to do. Continue rinsing. If product gets in the eyes, flush Eyes: eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately. Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists Skin: and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.

respiration. Seek immediate medical attention.

Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial

Inhalation:



Page 2 of 6 POC-9007C

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 1.1 SDS Revision Date: 12/14/2019

1.2		1	4. FIRST AID MEASURES –	- cont′d	
	Effects of Exposure:	Ingestion: Eyes:	cause lung damage. Irritation upon direct contact. Symptoms may	terial can enter the lungs during swallowing or vor include stinging, tearing, redness and swelling.	J
		Skin:	hazard. Toxic in contact with skin. Causes ski		
		Inhalation:	system. Symptoms of overexposure can incorporately breathing. Inhalation of concentrated vaporately systems.	tating to the nose, throat and other tissues of the reclude coughing, wheezing, nasal congestion, and ors can cause central nervous system depress. Odor may give some warning of exposure, but od	d difficultation (e.g.
3	Symptoms of Overexposure:	Ingestion: Eyes: Skin:		ching and watering. redness, itching, and irritation of affected areas.	
	A	Inhalation: Shortness of breath. May cause drowsiness or dizziness.			
.4 .5	Acute Health Effects: Chronic Health Effects:		if swallowed and enters airways. Causes skin in	rritation.	
.6	Target Organs:	Eyes, Skin, I	nage to organs.		
.7	Medical Conditions Aggravated		skin, eye, or respiratory disorders.	HEALTH	1
	by Exposure:		. , , , , , , , , , , , , , , , , , , ,	FLAMMABILITY	1
				PHYSICAL HAZARDS	0
				PROTECTIVE EQUIPMENT	В
				EYES SKIN LUNGS	
		until the fire Keep conta	ses if exposed to the heat of fire. Keep contain has been extinguished. Keep away from hea ainer closed. When exposed to high tem	at, lit cigarettes, sparks & open flame.	
.3	Extinguishing Methods: Firefighting Procedures:	water spray spray, fog or As in any demand) an spray to coo from fire coo	on products such as oxides of carbon (e.g., Cores, use dry chemical, carbon dioxide, water to cool fire-exposed containers. Water may be a ralcohol-resistant foam. Do NOT use straight stringing, wear MSHA/NIOSH approved self-contained full protective gear. Keep containers cool ure of fire-exposed surfaces and to protect personantrol or dilution from entering sewers, drains, Firefighters must use full bunker gear including	spray or alcohol-resistant foam. Use ineffective. For large fires, use water reams of water. sined breathing apparatus (pressurentil well after the fire is out. Use water al. Fight fire upwind. Prevent runoff drinking water supply, or any natural	0



Page 3 of 6

POC-9007C

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision Date: 12/14/2019 SDS Revision: 1.1 7. HANDLING & STORAGE INFORMATION 7 1 Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. 72 Storage & Handling: Keep this material away from heat, sparks and open flame. Pressurized container: Do not pierce or burn, even after use. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Storage temperature: 32-120 °F (0-49 °C). Take precautionary measures against static discharge. Store away from incompatible materials (see Section 10). 7.3 Special Precautions: Do not breathe fumes/mist/vapors/spray. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Exposure Limits: NOHSC OSHA OTHER 8.1 ppm (mg/m³) ES-STEL PEAK STEL IDLH CHEMICAL NAME(S) ES-TWA STEL BUTANE 1000 800 900 (800)1900 NF 900 NA 2-BUTOXYETHANOL 50 75 (20)96.9 NF 50 75 700 NF **PROPANE** 1000 NA NF NF 1000 NA 2100 8.2 Ventilation & Engineering When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans), to keep exposure below the airborne exposure limits. Ensure that an eyewash station, sink or washbasin is available in 8.3 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8.4 Eye Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Hand Protection: 8.5 If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.6 Body Protection: No special body protection is required under typical circumstances of use and handling. Wear appropriate protective clothing to prevent skin contact. (boots, lab coat, apron, coveralls) as needed. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES Appearance: Aerosol 9.2 Odor Solvent odor. Odor Threshold: 9.3 NA 9.4 NΑ 9.5 Melting Point/Freezing Point: NA 9.6 Initial Boiling Point/Boiling NA Range: 9.7 Flashpoint: NA 9.8 Upper/Lower Flammability NA Limits: 9.9 Vapor Pressure: NA 9.10 Vapor Density: NA Relative Density: 9.11 NA 9.12 Solubility: NA 9.13 Partition Coefficient (log Pow): NA 9.14 Autoignition Temperature NA 9.15 Decomposition Temperature: NΑ Viscosity: 9.16 NΑ 9.17 Other Information: NA 10. STABILITY & REACTIVITY Stability: Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition; however, relatively stable under ambient conditions when stored properly. 10.2 Hazardous Decomposition If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon & nitrogen). 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid Exposure to, or contact with, extreme temperatures, incompatible chemicals, direct sunlight, strong light sources, sparks, flame. 10.5 Incompatible Substances: Strong oxidizers, peroxides or strong acids or alkalis



Page 4 of 6 POC-9007C

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 1.1 SDS Revision Date: 12/14/2019 11. TOXICOLOGICAL INFORMATION Inhalation: YES 11.1 Routes of Entry: Absorption: YFS Ingestion: YES 112 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below. 2-Butoxyethanol – LD₅₀ (oral, rat): 470 mg/kg; LD₅₀ (dermal, rabbit): 400 mg/kg; LC₅₀ (inh, mouse, 4h): 700 ppm; Butane: LC₅₀ (inh, rat, 4h): 68,000 ppm; Sodium Dodecyl Sulphate: LD₅₀ (oral, rat): 1288 mg/kg; Propane: LC₅₀ (inh, rat, 4h): 800,000 ppm; 11.3 Acute Toxicity: May cause moderate eye and skin irritation. 11.4 Chronic Toxicity Long-term toxicological studies have not been conducted for this product. 11.5 Suspected Carcinogen: NA Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. 11.6 Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. 11.7 Irritancy of Product See Section 4.2 11.8 Biological Exposure Indices ΝE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: 12.1 Long-term ecological studies have not been conducted for this product. Effects on Plants & Animals 122 There are no specific data available for this product. An environmental fate analysis has not been conducted on this specific product 12.3 Effects on Aquatic Life: 2-Butoxyethanol - LC50 (Lepomis macrochirus, 96h): 1,490 mg/L; LC50 (Pimephales promelas, 96h): 2,137 mg/L 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 3. Dispose of in accordance with local, state, provincial and federal laws and regulations. Disposal of hazardous waste must be through by a licensed treatment, storage or disposal facility (TSDF). 13.2 Special Considerations: Aerosols may be managed as Universal Waste in some states (e.g., CA, CO, MN, etc.). Contact the federal, state or provincial environmental authority to determine suitability for recycling and or proper disposal requirements. U.S. EPA RCRA Characteristic Waste (Reactive): D003 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/20 14.2 IATA (AIR): UN1950, AEROSOLS, FLAMMABLE, 2.2 (LTD QTY, IP VOL ≤ 500 mL); or _γdΩ_Σ ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 820 mL) 14.3 IMDG (OCN): UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L) 14.4 TDGR (Canadian GND): UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L) ADR/RID (EU): 14.5 UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L); Transport Cat: 3; Tunnel Code: (E) 14.6 SCT (MEXICO): UN1950, AEROSOLES, 2.2 (CANT. LTDA., IP VOL ≤ 1.0 L) 14.7 ADGR (AUS):

UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1.0 L)



Page 5 of 6 POC-9007C

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards SDS Revision: 1.1 SDS Revision Date: 12/14/2019

		15. REGULATORY INFORMATION		
15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements.		
15.2	SARA TPQ:	There are no specific Threshold Planning Quantities for the components of this product.		
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.		
15.4	CERCLA Reportable Quantity:	NA		
15.5	Other Federal Requirements:	NA NA		
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS A, D2B (Compressed Gas, Other Toxic Effects).		
15.7	State Regulatory Information:	2-Butoxyethanol is listed on the following state criteria list(s): Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA). Butane and Propane are listed on the following state criteria list(s): MA, MN, NJ, PA, WA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous		
15.8	Other Requirements:	All components are either listed on the U.S. TSCA inventory or are not regulated under TSCA under 40 CFR § 720.30. Listed on AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) New Zealand Inventory of Chemicals (NZIoC) Registration Status: CAS 7732-18-5: Maybe used as a single component chemical under an appropriate group standard CAS 106-97-8: HSR000989 CAS 111-76-2: HSR001154 CAS 151-21-3: HSR003122 CAS 74-98-6: HSR001010 NZIoC Classification: 6.9A; Aerosols (Subsidiary Hazard) – HSR002519 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)		
		16. OTHER INFORMATION		
16.1	Other Information:	DANGER! PRESSURIZED CONTAINER: MAY BURST IF HEATED. CAUSES MILD SKIN IRRITATION. CAUSES EYE IRRITATION. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Pressurized container: Do not pierce or burn, even after use. Wash affected areas thoroughly after handling. Do no eat, drink or smoke when using this product. Wear protective gloves/eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to appropriate waste disposal facility in accordance with local, regional, national, international regulations. KEEP OUT OF REACH OF CHILDREN.		
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.		
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's, Smarter Sorting's & Petra Oil Company's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.		
16.4	Prepared for:	Petra Oil Company 50 Jacobs Lane Ngaruawahia 3792, New Zealand Tel: +64 (21) 771 703 Email: agacita@petraoilco.com		



Page 6 of 6 POC-9007C

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.1

SDS Revision Date: 12/14/2019

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists	
IDLH	H Immediately Dangerous to Life and Health	
NOHSC	National Occupational Health and Safety Commission (Australia)	
OSHA	U.S. Occupational Safety and Health Administration	
PEL	Permissible Exposure Limit	
STEL	Short Term Exposure Limit	
TLV	Threshold Limit Value	
TWA	Time Weighted Average	

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	



PERSONAL PROTECTION RATINGS:

Α			
В			
С		H.	
D		THE TABLE	
Е			
F		HA.	





OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic	
Irrit	Irritant	
NA	Not Available	
NR	No Results	
ND	Not Determined	
NE	Not Established	
NF	Not Found	
SCBA	Self-Contained Breathing Apparatus	
Sens	Sensitization	
STOT RE	Specific Target Organ Toxicity – Repeat Exposure	
STOT SE	Specific Target Organ Toxicity – Single Exposure	

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:	
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard	FLAMMABILITY
1	Slight Hazard	\
2	Moderate Hazard	REACTIVITY
3	Severe Hazard	
4	Extreme Hazard	
ACD	Acidic	
ALK	Alkaline	
COR	Corrosive	/ ~~~
w	Use No Water	HEALTH 🔪
ОХ	Oxidizer	SPECIAL
TREFOIL	Radioactive	PRECAUTIONS

TOXICOLOGICAL INFORMATION:

imals mal
mal

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System	
DOT	U.S. Department of Transportation	
TC	Transport Canada	
EPA	U.S. Environmental Protection Agency	
DSL	Canadian Domestic Substance List	
NDSL	Canadian Non-Domestic Substance List	
PSL	Canadian Priority Substances List	
TSCA	U.S. Toxic Substance Control Act	
EU	EU European Union (European Union Directive 67/548/EEC)	
WGK	Wassergefährdungsklassen (German Water Hazard Class)	

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	®			Θ	®		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\limits		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment